



SONDEX OVERVIEW

High temperature battery packs for memory production logging tools

BENEFITS

Dependable data capture, where failure isn't an option, requires highly reliable battery packs to meet demanding power requirements.

By choosing Custom Power you can be assured of safe and reliable power in the most extreme environments, with operating temperatures up to 200°C.

We are firmly established as the premier manufacturer of high temperature lithium battery packs for the downhole oil and gas industry, providing power for many applications including memory.

WHY CHOOSE CUSTOM POWER?

-  Highly competitive pricing.
-  UN3090 certified for air transport.
-  Fast delivery and worldwide shipping.
-  High quality battery packs manufactured in the US.
-  Endorsed by OEM & preferred battery supplier to SONDEX.

Part	OCV	Capacity	Operating Temperature	Cell Type	Max Continuous Current	Dimensions (mm)*	Connection
BAT-01	Use BAT-05						
BAT-02	18.0V	5.0Ah	50°C to 180°C	25-48-180MR 4266	100mA	(L) 340 x (D) 28.75	Two Flying Leads ^a
BAT-03	19.5V	6.2Ah	-20°C to 150°C	PMX150 3B3700	500mA	(L) 328 x (D) 26.50	Sondex Threaded End
BAT-04	18.0V	5.0Ah	50°C to 180°C	25-48-180MR 4266	100mA	(L) 328 x (D) 26.50	Sondex Threaded End
BAT-05	19.5V	6.2Ah	-20°C to 150°C	PMX150 3B3700	500mA	(L) 340 x (D) 28.75	Two Flying Leads ^a
BAT-07	19.5V	6.2Ah	-20°C to 165°C	PMX165 3B5100	500mA	(L) 340 x (D) 28.75	Two Flying Leads ^a
BAT-08	18.0V	4.5Ah	70°C to 200°C	VHT200 3B4800	250mA	(L) 340 x (D) 28.75	Two Flying Leads ^a
BAT-09	19.5V	6.2Ah	-20°C to 165°C	PMX165 3B5100	500mA	(L) 328 x (D) 26.50	Sondex Threaded End
BAT-10	19.5V	13.0Ah	-20°C to 165°C	PMX165 3B5200	500mA	(L) 600 x (D) 26.50	Sondex Threaded End
BAT-10	19.5V	13.0Ah	-20°C to 165°C	PMX165 3B5200	500mA	(L) 600 x (D) 28.75	Two Flying Leads ^a
BAT-11	7.8V	6.2Ah	-20°C to 165°C	PMX165 3B5100	500mA	(L) 117 x (D) 26.50	Two Flying Leads ^a
BAT-13	19.5V	26Ah	-20°C to 165°C	PMX165 3B5200	500mA	(L) 1130 x (D) 26.50	Sondex Threaded End
BAT-15	18.0V	4.5Ah	70°C to 200°C	VHT200 3B4800	250mA	(L) 328 x (D) 26.50	Sondex Threaded End
* All dimensions are nominal a Banana Male & Burndy Female Connector b Male & Female Burndy Connector for HADES Tool.							



CPUS SONDEX OVERVIEW V01.pdf

Technical specifications are subject to change without notice.
E & OE Issue A.

